



SR-15E3 IWS CARBINE MOD 2



SR-15 E3 IWS CARBINE MOD 2

P/N: 31030

Barrel	16" 1:7 Twist, Hammer Forged, Chrome Lined
Caliber	5.56 mm
Weight	6.60 lbs
Length	33.5"-36.5"



HAMMER FORGED



AMBIDEXTRIOUS CONTROLS



MULTI LUG IMPROVED E3 BOLT



UPPER RECEIVER EXTENDING
FREE-FLOATING BARREL SYSTEM



2 STAGE MATCH TRIGGER



QDC QUICK DISCONNECT
COUPLING

FOR MORE INFO CONTACT:

salesteam@knightarmco.com
phone (321) 607-9900
fax (321) 383-2143
www.KnightArmCo.com

701 Columbia Blvd.
 Titusville, FL 32780

The Knight's Armament Company SR-15 line represents the pinnacle of firearms based upon the Eugene Stoner designed operating system. The Mod 2's 16" chrome lined, 5.56mm NATO barrel is manufactured to military specifications, and features a proprietary mid-length gas system that increases reliability and durability while also reducing felt recoil. An improved E3 round-lug bolt design both enhances function and increases bolt life far beyond the industry standard. An ambidextrous bolt release, selector, and magazine release offer left-handed users the ergonomic advantages inherent to AR15-based controls, as well as giving right-handed users alternative methods of manipulation to increase efficiency of movement. The drop-in two-stage trigger serves double duty as an aid to long range precision marksmanship while enabling surgical speed shooting at close range.

SR-15E3 IWS CARBINE MOD 2



5.56mm 3-Prong Flash Eliminator: This improved design interferes with propellant gas combustion forward of the muzzle to significantly reduce flash signature. The flash hider's unique 3-prong configuration does not ring upon firing or when struck. Integral Quick Detach Coupling mounting detents support KAC's line of QDC sound suppressors for consistent and minimized point-of-impact shift.



URX 4 Handguard: Keymod accessory mounting points on 7 sides of the handguard for attachment of ancillary devices with less weight and bulk than MIL-STD-1913 rail attachment methods. The URX4 has lower weight, reduced girth, and improved cooling characteristics compared to other handguard designs. 14.5" length fully protects and free floats the barrel while offering optimal hand placement options for full spectrum application along with the ability to precisely mount accessories. An integral 1913 top rail provides traditional mounting confidence for forward-placed aiming devices and night vision.



Mod 2 Gas System: Minimizes leakage, ensuring more consistent operation in harsh conditions, with or without an attached sound suppressor. The Mod 2 gas block is secured with a locking ring, resulting in a more rigid barrel due to the elimination of the taper pin grooves, and does not require individually fit gas blocks.



Receiver End Plate with Ambidextrous QD Sling Swivel Sockets, 6-Position Collapsible SOPMOD Stock, Fully Ambidextrous Lower Receiver Controls, Extended Charging Handle Latch, Folding Front and 200-600 Meter Rear Micro Iron Sights are standard features of the SR-15E3 Mod 2.